

チーエル®パイプ重量表

●S. SJ

単位：kg

呼び径 種類と長さ	20A	25A	40A	50A	80A	100A	150A	200A
S 0100	1.8	2.8	3.9	4.7	6.76	8.25	16.7	22.3
S 0200	2.2	3.2	4.4	5.4	7.7	9.7	18.8	25.9
S 0300	2.2	3.4	4.83	5.93	8.43	10.8	21.2	28.8
S 0400	2.36	3.66	5.26	6.5	9.5	12	23	31.8
S 0500	2.6	4	5.7	7.2	10.4	13.3	25.2	34.7
S 0600	2.8	4.2	6.23	7.7	11.5	14.5	27.8	38.5
S 0700	2.93	4.53	6.66	8.2	12.3	16	29.8	41.7
S 0800	3.2	4.73	7.03	8.86	13.3	17	31.5	44.4
S 0900	3.4	5	7.26	9.5	14.5	18.5	34	48.1
S 1000	3.7	5.4	7.9	10.1	15.5	20.1	36.2	51
S 1500	4.7	6.8	10.1	13.1	20.4	26.7	47	66
S 2000	5.7	8.1	12.2	16	25.2	33.2	57.8	85
S 2500	6.7	9.4	14.4	18.9	30	39.7	68.6	100
S 3000	7.7	10.7	16.6	21.7	34.8	46.2	79.4	115
S 3500	8.7	12	18.8	24.6	39.7	52.7	—	—
SJ 1000	11	15	21	24	35	43	70	100
SJ 1500	14	19	28	32	48	59	96	138
SJ 2000	17	23	35	40	60	75	122	175
SJ 2500	20	27	42	48	72	90	148	210
SJ 3000	23	31	49	56	85	105	174	—
SJ 3500	25	35	55	64	97	120	—	—

●L. B. T. X. CF. CA. R. RT

単位：kg

呼び径と大口径 種類と小口径	20A	25A	40A	50A	80A	100A	150A	200A
L	2.15	3.2	4.8	5.8	9.9	13.3	24.8	46
B	1.8	3	4.1	5.2	8.8	11.5	22.9	36
T	3.1	4.7	7.3	8.6	14.1	20.2	37	63
X	4.1	6.6	9	11.6	18.8	23.9	—	—
CF	0.8	1.3	1.7	3	—	—	—	—
CA	—	—	—	—	3.7	5	9.6	15
R 020A	—	2.2	3.1	3.6	5.9	—	—	—
R 025A	—	—	4.1	4.1	5.9	—	—	—
R 040A	—	—	—	4.5	6.4	—	—	—
R 050A	—	—	—	—	6.7	8.3	—	—
R 080A	—	—	—	—	—	9.2	16.2	23.3
R 100A	—	—	—	—	—	—	14.7	24.8
R 150A	—	—	—	—	—	—	—	31.1
RT 020A	—	4.5	4.8	7.4	11.6	—	—	—
RT 025A	—	—	6.3	7.7	12.2	—	—	—
RT 040A	—	—	—	8.4	12.1	—	—	—
RT 050A	—	—	—	—	13	17.2	—	—
RT 080A	—	—	—	—	—	18.5	31	55
RT 100A	—	—	—	—	—	—	32	63
RT 150A	—	—	—	—	—	—	—	67